

Flexible Copper Braid Bond



Copper Braid with Tinned (1 Hole)

Code No.	Amp Rating (A)	No. of Layer	Length (mm)	Cross Section (mm ²)	Weight (kg)
LZFCB 502001	200	1	200	50	0.12
LZFCB 503001	200	1	300	50	0.16
LZFCB 504001	200	1	400	50	0.21

Application : Suitable for bonding of metal door, gate, fence, etc., where flexibility is required or the bond is subject to movements.

Material : High conductivity copper wire with tinned



Copper Braid with Tinned (2 Hole)

Code No.	Amp Rating (A)	No. of Layer	Length (mm)	Cross Section (mm ²)	Weight (kg)
LZFTB 353501	150	1	350	35	0.15
LZFTB 503501	200	1	350	50	0.18
LZFTB 703501	250	1	350	70	0.25
LZFTB 953501	300	1	350	95	0.35
LZFTB 1203501	360	1	350	120	0.42
KGZFCB 39533	700	3	386	150	0.60

Application : Suitable for bonding of metal door, gate, fence, etc., where flexibility is required or the bond is subject to movements.

Material : High conductivity copper wire with tinned



Copper Braid with Tinned (Round Type)

Code No.	Amp Rating (A)	Length (mm)	Cross Section (mm ²)	Weight (kg)
GRB20 - 350	480	350	150	0.75
GRB20 - 1000	480	1000	150	2.15

Application : Suitable for bonding of metal door, gate, fence, etc., where flexibility is required or the bond is subject to movements.

Material : High conductivity copper wire with tinned

Special size can be requested.