

Coupling



For Threaded Type

Code No.	Rod Ø (in)	Length (mm)	Weight (kg)
GRBCO 12	1/2	64	0.07
GRBCO 58	5/8	64	0.09
GRBCO 34	3/4	70	0.14
GRBCO 1	1	90	0.25

Tested : IEC 62561 - 2

Application : Extend to the length of ground rod

Material : High Strength Silicon Bronze

Driving Head



For Threaded Type

Code No.	Rod Ø (in)	Weight (kg)
GRBDH 12	1/2	0.06
GRBDH 58	5/8	0.09
GRBDH 34	3/4	0.16
GRBDH 1	1	0.35

Tested : IEC 62561 - 2

Application : Protect the top of ground rod while driving

Material : High Tensile Steel



For Standard Type


Code No.	Rod Ø (in)	Weight (kg)
GRDSR 12	1/2	0.13
GRDSR 58	5/8	0.16
GRDSR 34	3/4	0.19
GRDSR 1	1	0.30

Tested : IEC 62561 - 2

Application : Protect the top of ground rod while driving

Material : Zinc-plated Steel

Tip



For Threaded Type

Code No.	Rod Ø (in)	Weight (kg)
GRTTR 12	1/2	0.025
GRTTR 58	5/8	0.030
GRTTR 34	3/4	0.070
GRTTR 1	1	0.10

Application : Lead the ground rod into the hard soil area

Material : High Tensile Steel