

**DIN 300**



**ΔIn : 30 mA - 30 A (max)**



Output Contact



**Products Feature : DIN 300 / 300E**

- Selectable earth leakage sensitivity between 30 mA - 30 A.
- Selectable time delay between 0 msec - 3 sec
- Earth leakage level indicator on panel
- Detection of no connection with ZCT
- Output relay trip indicator
- Trip starting indicator
- Protected against nuisance tripping

**DIN 300E**



50% Pre Fault Output Contact



Output Contact

**Products More Feature : DIN 300E (ONLY)**

- 50% Pre-Fault Output Contact
- Remote Test and Remote Reset Functions

รุ่น	DIN 300-240A	DIN 300E-240A
<b>SPECIFICATIONS</b>		
<b>SETTINGS</b>		
Sensitivity Adjustment	30mA, 50mA, 75mA, 100mA, 125mA, 150mA, 200mA, 250mA, 300mA, 500mA, 750mA, 1A, 1.25A, 1.5A, 2A, 2.5A, 3A, 5A, 7.5A, 10A, 12.5A, 15A, 20A, 25A, 30A (max)	
Delay Time Adjustment	Instantaneous, 50 ms, 100 ms, 150 ms, 25 ms, 350 ms, 500 ms, 1 s, 3 s	
<b>CONTACTS</b>		
Contact Arrangement	Change-Over	
Contact Rating	5A, 250 VAC (Cos φ = 1) for Tripping Contact 5A, 250 VAC (Cos φ = 1) for 50% Pre-Fault Contact *	
Contact Material	Silver Alloy	
Operating Time	15 ms max	
Expected Electrical Life	100,000 operations at rated current	
Expected Mechanical Life	5 x 10 <sup>6</sup> operations	
Approval	UL / CSA / VDE / TUV / SEMKO	
<b>INPUTS</b>		
Remote Test / Reset Inputs	NO Dry Contact	
<b>AUXILIARY SUPPLY</b>		
Supply Voltage	198 - 265 VAC, 50/60 Hz	
VA Rating	3 VA typical	
<b>INDICATORS and DIMENSION</b>		
Auxiliary Supply	Green Colour LED Indicator	
Time Delay	Red Colour LED Indicator	
Trip	Red Colour LED Indicator	
Leakage Current	5 Red Indicator for leakage level	
Dimension	DIN Rail 71 x 85 mm.	
<b>Price</b>		
ราคา	<b>5,250.-</b>	<b>7,500.-</b>