

Mini Contactor Relays



พิกัดกระแส (AC-3)		คอนแทคช่วย	แรงดันคอยด์	รหัสสินค้า	ราคา (บาท)
380/400VAC	KW				
DILEM Mini Contactor					
6.6	3	1 N/O	24VDC	DILEEM-10-G(24VDC)	900
6.6	3	1 N/C		DILEEM-01-G(24VDC)	900
9	4	1 N/O		DILEM-10-G(24VDC)	1,050
9	4	1 N/C		DILEM-01-G(24VDC)	1,050
12	5.5	1 N/O		DILEM-12-10-G(24VDC)	1,650
12	5.5	1 N/C		DILEM-12-01-G(24VDC)	1,650
6.6	3	1 N/O	230VAC	DILEEM-10(230V50Hz)	650
6.6	3	1 N/C		DILEEM-01(230V50Hz)	650
9	4	1 N/O		DILEM-10(230V50Hz)	700
9	4	1 N/C		DILEM-01(230V50Hz)	700
12	5.5	1 N/O		DILEM12-10(230V50Hz)	950
12	5.5	1 N/C		DILEM12-01(230V50Hz)	950
Mini Contactor 4 Pole					
9	4		24VDC	DILEM4-G(24VDC)	1,150
9	4		230VAC	DILEM4(230V50Hz)	800

พิกัดกระแส (AC-3)		คอนแทคบล็อก	ใช้กับรุ่น	รหัสสินค้า	ราคา (บาท)
380/400VAC	KW				
Auxiliary contact					
		2 N/O	DILEEM, DILEM, DILEM12, DILEM4, DILER	20DILE	230
		1 N/O, 1 N/C		11DILE	230
		2 N/C		02DILE	230
		1 N/O, 1 N/C		11DDILE	520
		4 N/O		40DILE	400
		1 N/O, 3 N/C		13DILE	400
		2 N/O, 2 N/C		22DILE	400
		3 N/O, 1N/C		31DILE	400
		4 N/C		04DILE	400
		2 N/O, 2 N/C		22DDILE	710



Overload Relay - ZE				
ย่านการปรับค่ากระแส (A)	ใช้กับคอนแทคเตอร์รุ่น	คอนแทคช่วย	สสินค้า	ราคา (บาท)
0.1-0.16	DILEM..(ไม่สามารถใช้กับแมกเนติครัน DILEEM ได้)	1 N/O + 1 N/C	ZE-0,16	1,000
0.16-0.24		1 N/O + 1 N/C	ZE-0,24	1,000
0.24-0.4		1 N/O + 1 N/C	ZE-0,4	1,000
0.4-0.6		1 N/O + 1 N/C	ZE-0,6	1,000
0.6-1		1 N/O + 1 N/C	ZE-1,0	1,000
1-1.6		1 N/O + 1 N/C	ZE-1,6	1,000
1.6-2.4		1 N/O + 1 N/C	ZE-2,4	1,000
2.4-4		1 N/O + 1 N/C	ZE-4	1,000
4-6		1 N/O + 1 N/C	ZE-6	1,000
6-9		1 N/O + 1 N/C	ZE-9	1,000
9-12		1 N/O + 1 N/C	ZE-12	1,000

